

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS

1 (Canceled)

2. (Currently Amended) A seat assembly ~~according to claim 1, further comprising for a vehicle comprising:~~

a seatback;

a seat cushion;

a four-link mechanism for supporting the seat cushion;

a drive unit for driving the four-link mechanism and moving the seat cushion between a seating position and a stowed position; wherein when the seat cushion is moved between the seating position and the stowed position, support of the seat cushion is maintained by operation of the four-link mechanism and the drive unit; and

a control unit for operating the drive unit, wherein the drive unit includes a first drive unit for moving the seat cushion and a second drive unit for moving the seatback, and the first drive unit and the second drive unit operate in association with each other for simultaneously operating the seat cushion and the seatback.

3 (Canceled)

4. (Original) A seat assembly according to claim 2, wherein the first drive unit is attached to one of cushion side frames forming the seat cushion and the second drive unit is attached to one of backside frames forming the seatback.

5. (Previously Presented) A seat assembly according to claim 4, wherein the four-link mechanism includes a first pair of links rotatably connected to the respective cushion side frames via a first rotational shaft and to a vehicle floor via a second rotational shaft, and a second pair of links rotatably connected to the respective cushion side frames via a third rotational shaft and to the vehicle floor via a fourth rotational shaft.

6. (Original) A seat assembly according to claim 5, wherein the first pair of links are connected with each other via the first rotational shaft.

7. (Original) A seat assembly according to claim 6, wherein the first drive unit includes a first motor and a first deceleration mechanism and the second drive unit includes a second motor and a second deceleration mechanism.

8. (Original) A seat assembly according to claim 7, wherein the first drive unit further includes a pinion which is rotated by the first motor and the first deceleration mechanism and which engages with a gear fixed to the first rotational shaft.

9. (Canceled)

10. (Canceled)

11. (Canceled)

12. (Currently Amended) A seat assembly ~~according to claim 11, further~~
comprising for a vehicle comprising:

a seatback;

a seat cushion;

a link mechanism supporting the seat cushion; and

a motor-operated drive unit for driving the link mechanism and moving the
seat cushion between a seating position and a stowed position, wherein when the
seat cushion is moved between the seating position and the stowed position, support
of the seat cushion is maintained by operation of the link mechanism and the drive
unit; and

a control unit for operating the motor-operated drive unit, wherein the drive
unit includes a first drive unit for moving the seat cushion and a second drive unit for
moving the seatback, and the first drive unit and the second drive unit operate in
association with each other for simultaneously operating the seat cushion and the
seatback.

13. (Currently Amended) A seat assembly ~~according to claim 11, for a~~
vehicle comprising:

a seatback;

a seat cushion;

a link mechanism supporting the seat cushion; and
a motor-operated drive unit for driving the link mechanism and moving the
seat cushion between a seating position and a stowed position, wherein when the
seat cushion is moved between the seating position and the stowed position, support
of the seat cushion is maintained by operation of the link mechanism and the drive
unit; and

wherein the link mechanism is a four-link mechanism and includes a first link mechanism for moving the seat cushion and a second link mechanism for simultaneously moving the first link mechanism and the seatback.

14. (Previously Presented) A seat assembly according to claim 12, wherein the first drive unit is attached to one of cushion side frames forming the seat cushion and the second drive unit is attached to one of backside frames forming the seatback.

15. (Previously Presented) A seat assembly according to Claim 14, wherein the link mechanism is a four-link mechanism and includes a first pair of links rotatably connected to the respective cushion side frames via a first rotational shaft and to a vehicle floor via a second rotational shaft, and a second pair of links rotatably connected to the respective cushion side frames via a third rotational shaft and to the vehicle floor via a fourth rotational shaft.

16. (Currently Amended) A seat assembly according to claim 15 5, wherein the first pair of links are connected with each other via the first rotational shaft.

17. (Previously Presented) A seat assembly according to claim 16, wherein the first drive unit includes a first motor and a first deceleration mechanism and the second drive unit includes a second motor and a second deceleration mechanism.

18. (Previously Presented) A seat assembly according to claim 17, wherein the first drive unit further includes a pinion which is rotated by the first motor and the first deceleration mechanism and which engages with a gear fixed to the first rotational shaft.

19. (Previously Presented) A seat assembly according to claim 13, wherein the first link mechanism includes a first pair of links rotatably connected to the seat cushion via a first rotational shaft and to a vehicle floor via a second rotational shaft, and a second pair of links rotatably connected to the seat cushion via a third rotational shaft and to the vehicle floor via a four rotational shaft.

20. (Previously Presented) A seat assembly according to claim 19, wherein the second link mechanism connects the seatback and the second pair of links.